



Fig.: Order No. 50054 with four spring-mounted brake rollers, order No. 50068.

## Single-sided work platform made of aluminium

Stable welded construction made of round aluminium tubes, upper standing surface 410 x 300 mm for comfortable and safe standing. End of side-rails fitted with non-slip plastic shoes.

Shipment in disassembled parts. Assembly instructions enclosed.

### Step and platform construction: Grooved aluminium

Working reach up to approx. m	2,50	2,70	3,00
Number of steps	2	3	4
Top tread w/d mm	410 x 300	410 x 300	410 x 300
Platform height mm	490	725	970
Standing surface on ground w/d mm	535/525	590/770	635/1000
Weight approx. kg	5,3	7,9	10,5
Order No.	50050	50051	50052



Fig.: Order No. 50056

### Step and platform construction: Wood

Working reach up to approx. m	2,50	2,70	3,00
Number of steps	2	3	4
Top tread w/d mm	410 x 300	410 x 300	410 x 300
Platform height mm	490	725	970
Standing surface on ground w/d mm	535/525	590/770	635/1000
Weight approx. kg	6,8	10,5	12,3
Order No.	50056	50057	50058



Fig.: Order No.50052

### Step and platform construction: Steel grating

Working reach up to approx. m	2,50	2,70	3,00
Number of steps	2	3	4
Top tread w/d mm	410 x 300	410 x 300	410 x 300
Platform height mm	490	725	970
Standing surface on ground w/d mm	535/525	590/770	635/1000
Weight approx. kg	7,9	11,8	15,0
Order No.	50053	50054	50055



Fig.: Order No. 50068/50069

## Accessories:

	Order No.
1 set = four spring-loaded-braking castors Diam. 50 mm for self-installation	550068 Suitable for platforms with two steps.
1 set = four spring-loaded-braking castors Diam. 50 mm for self-installation	50069 Suitable for platforms with three to four steps.