

# PLATFORM LADDERS

GS tested in accordance with German Ordinance on Industrial Safety (BetrSichV), TRBS 2121, action manual BGI 694, in conformity with European Standard DIN EN 131-7 (replacing BGI 637).



## Folding work platform made of aluminium movable

Sturdy profile spars, 80mm deep, grooved steps, permanently edged to the spars, spacious platform 650 x 600mm made of grooved aluminium cover, handrail on both sides, three-sided platform railing.

Safe stand ensured by non-slip nivello® ladder shoes and stabiliser with 2 lockable castors 125 mm dia. with large tray on top. Ladder width 650 mm.



Fig. Order No. 52310

Working reach up to approx. m	3,15	3,40	3,60	3,85	4,30	4,80	5,25
Platform height m	1,15	1,38	1,61	1,84	2,30	2,77	3,23
Height incl. railing m	2,15	2,38	2,61	2,84	3,30	3,77	4,23
Folded total length m	2,75	3,00	3,25	3,50	4,00	4,50	5,00
Base spread m	1,40	1,50	1,60	1,70	1,95	2,20	2,40
Width of cross tube	1,00	1,00	1,35	1,35	1,70	1,90	1,95
Number of steps incl. platform	5	6	7	8	10	12	14
Weight approx. kg	37,0	39,0	43,0	45,0	49,0	55,0	76,0
Order No.	52305	52306	52307	52308	52310	52312	52314

## Folding work platform made of aluminium movable with small stabiliser bar

Sturdy profile spars, 80 mm deep, grooved steps, permanently edged to the spars, spacious platform 650 x 600mm made of grooved aluminium cover, handrail on both sides, three-sided platform railing.

Safe stand ensured by non-slip nivello® ladder shoes and small stabiliser bar with ballast weight, with 2 lockable castors 125 mm dia. with large tray on top. Ladder width 650 mm.

The small stabiliser bar is particularly suitable for narrow shelf aisles and for use in other constricted room. Ballast weights ensure the required stability. Assembly instructions attached.

Working reach up to approx. m	3,15	3,40	3,60	3,85	4,30	4,80	5,25
Platform height m	1,15	1,38	1,61	1,84	2,30	2,77	3,23
Height incl. railing m	2,15	2,38	2,61	2,84	3,30	3,77	4,23
Folded total length m	2,75	3,00	3,25	3,50	4,00	4,50	5,00
Base spread m	1,40	1,50	1,60	1,70	1,95	2,20	2,40
Width of cross tube	0,85	0,85	0,85	0,85	1,00	1,00	1,00
Number of steps incl. platform	5	6	7	8	10	12	14
Ballast weight approx. kg	30,0	50,0	60,0	80,0	100,0	150,0	160,0
Weight w. ballast approx. kg	67,0	89,0	103,0	125,0	149,0	205,0	218,0
Order No.	52705	52706	52707	52708	52710	52712	52714



Fig. Order No. 52712



Fig. Ballast weight 80 kg